



LEGEND

- A. CONDUCTOR - #12AWG (19 X #25AWG) SILVER PLATED COPPER
- B. SEMI-CONDUCTIVE SILICONE
- E. SILICONE RUBBER, WHITE TO $\phi 0.360 \pm 0.015$

RATING: 20 KVAC, RMS, 60 HZ
60 KVDC

REVISIONS				THIS DOCUMENT AND THE INFORMATION CONTAINED IN IT ARE THE PROPERTY OF DIELECTRIC SCIENCES, INC AND SHALL NOT BE REPRODUCED OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OF APPARATUS WITHOUT PERMISSION.			
REV	ECO NUMBER	APPD	DATE	UNLESS OTHERWISE SPECIFIED	DRAWN JAG	DATE 01MAR73	DIELECTRIC SCIENCES, INC CHELMSFORD, MASSACHUSETTS 01824
-	RELEASE DRAWING			DIMENSIONS ARE IN INCHES TOLERANCE ON	CHECKED	DATE	
				DECIMALS .XX ±.01 .XXX ±.005	APPROVED	DATE	CABLE: 1/C 12AWG, 60KVDC
				ANGLES ±	MATERIAL		
				CONCENTRICITY .005 TIR REMOVE BURRS & SHARP EDGES ALL MACHINE SURFACES 125√	FINISH		SIZE A
				⊙ ◁			FSCM NO. 50509
							DWG NO. 2024
							REV
					SCALE		SHEET 1 OF 1